

412/SP25

Set of 25 twist drills, HSS,
with cylindrical shanks
in case

Ø 1÷13 x 0,5 mm

$R \leq 800 \text{ N/mm}^2$
 $HV \approx 750 \div 820$
DIN 338



≡ 110x190x55 mm



004120425

437U/09

Assortment
for repairing
damaged threads
in metal case

M5X0,8
M6X1,0
M8X1,25
M10X1,5
M12X1,75

≡ 370x230x55 mm



2 kg

004370550

450/C21

Assortment of holesaws and
accessories for industrial use

	450	Ø 19-22-29-35-38-44-51-57-64-76 83-92-95-105-114 mm
	450AL	/1 - /2
	450PA	/1 - /2
	450PR	
	450AD	



21x

Co8%

≡ 420x280x60 mm

7 kg

004500315

446/C110

Assortment of 105 chrome-steel taps
and dies, metric thread,
and 5 accessories for car repair jobs,
in wooden case

435/0 444/1 436/1
435/3 444/2



≡ 500x337x60 mm

8,1 kg


004460060

430 M mm	433 M mm	440/440A M mm	441/441A M mm
2x0,4	6x0,75 - 7x0,75	2x0,4	6x0,75 - 7x0,75
3x0,5	8x0,75 - 8x1	3x0,5	8x0,75 - 8x1
4x0,7	9x0,75 - 9x1	4x0,7	9x0,75 - 9x1
5x0,8	10x0,75 - 10x1	5x0,8	10x0,75 - 10x1
6x1	10x1,25 - 11x0,75	6x1	10x1,25 - 11x0,75
7x1	11x1 - 11x1,25	7x1	11x1 - 11x1,25
8x1,25	12x0,75 - 12x1	8x1,25	12x0,75 - 12x1
9x1,25	12x1,25 - 12x1,5	9x1,25	12x1,25 - 12x1,5
10x1,5	14x1 - 14x1,25	10x1,5	14x1 - 14x1,25
11x1,5	14x1,5 - 16x1	11x1,5	14x1,5 - 16x1
12x1,75	16x1,5 - 18x1,5	12x1,75	16x1,5 - 18x1,5
14x2		14x2	
16x2		16x2	

1599F

Parallel bench vices, forged

Fully steel cast. Milled and hardened jaw surface.
Front opening. High clamping depth.



A max



	L mm	BxH mm	Ø mm	A max mm	
1599F/100	100	92x46	11	125	015990100
1599F/125	125	108x54	13	150	015990125
1599F/150	150	125x62	13	200	015990150
1599F/175	175	140X70	15	220	015990175